

UNDERMOUNT INSTALLATION INSTRUCTIONS

1. Inspect sink for damage and dimensional compatibility. Do not attempt to install a damaged sink.
 2. Undermount sinks are designed for use with solid surface benchtops, examples as follows;
 - Natural Stone eg. Marble, Quartz etc
 - Engineered stone eg. CaesarStone, Silestone etc
 - Acrylic solid surfaces eg. Corian, Freestyle, Staron etc
 It is not recommended that undermount sinks be fitted to laminate benchtops.
 3. Contact your benchtop supplier to establish the type of material used. Your supplier should recommend a suitable adhesive and sealant for the specified material.
 4. Mark the exact location of the cutout in the benchtop. Ensure that the tap location is suitable. Ensure that the supplied cutout gives the desired fit.
 5. Using the appropriate tools and safety equipment, cut the benchtop as marked out.
 6. Mask the sink and the cutout to avoid sealant/epoxy overspill onto finished surfaces.
 7. Apply the recommended sealant at the edge of the join between sink and benchtop.
 8. Apply the recommended adhesive as directed by adhesive supplier.
 9. Position the sink in the desired final location and clamp to the benchtop.
 10. Promptly remove excess sealant from benchtop and sink using a recommended cleanup solvent suitable for your benchtop material and stainless steel.
 11. When the installation has cured for the recommended period check that the seal is watertight and the attachment is secure.
- Dorf Clark bears no responsibility for faulty installation and the effects thereof.

OVERMOUNT INSTALLATION INSTRUCTIONS

1. Using knife or scissors cut out the relevant perforated insert from the inner carton.
2. Position the template on the bench top and trace around with a pencil. Check the size against the overall cutout dimensions before commencing cutting.
3. Cutout the bench top carefully following the inside edge of the pencil line. An exact cut is required to obtain the best fit.
4. For normal thickness bench tops, the attached fixing clips should be suitable (*refer Figure A*). If the thickness of the bench top exceeds the range of the fixing clips then extension clips can be purchased and mounted onto the clip brackets. *Refer Figure B*.
5. Position the sink in the cut out hole and align properly. The fixing clips can be bent out of the way to assist installation (*refer Figure C*). Check that the sink sealing tape will seal evenly around the edge of the hole.
6. Remove the sink and if required install the waste assemblies and the tap. It is suggested that silicone sealant be applied between the waste grate and the sink outlet hole.
7. Remove the protective backing from the sealing tape, apply a continuous bead of silicone sealant between the sealing tape and the edge of the sink and quickly place into position.
8. Bend the fixing clips straight so that the legs clear the hinge area. Tighten the clips evenly using a low torque setting (*refer Figure D*). Note: over tightening the clip may strip the thread.
9. Plumb up the tap and waste fittings.




FIGURE A




FIGURE B



FIGURE C




FIGURE D