

TASMAN II - HAND SHOWER

WATER EFFICIENT TAPWARE

(NOMINAL FLOW RATE = 8 L/min)

PLUMBERS INSTALLATION INSTRUCTIONS

Important

- * Shower bracket (2) is fitted with a 9L/min flow regulated check valve(6) and also includes an additional check valve(5). Ensure both arrows of the check valves are pointing in the direction of water flow.

 Note: Warranty is void if check valve (5) & flow regulated check valve (6) are not installed as shown.
- * Not suitable for gravity feed systems.
- * All pipework must be thoroughly flushed prior to installation, as foreign materials may block the flow regulating device and reduce the flow of water.

Installation

- Check that the threaded nipple(3) is correct length as shown. Cut to length if required ensuring end face is square. Apply thread tape to the thread.
 Important: Care must be taken that thread tape cannot become dislodged and block the flow regulating device, causing a reduction in water flow.
- Fit 'O'ring (4) into base of shower bracket (2). Screw the shower bracket(2) onto the threaded nipple and tighten. Position as required. DO NOT OVERTIGHTEN.
- 3) Fit rubber washer (7) into the end of the shower hose (8). Screw hexagon end of the shower hose (8) onto the outlet end of the shower bracket (2) and tighten. Screw swivel cone end of the shower hose (8) onto the handshower (1) and fit the handshower (1) into the shower bracket(2).

 Important:If water does not flow from shower head (1) make sure that check valves (5 & 6) are installed with the arrows pointing in the direction of flow.

SHOWER HEAD - THREE-FUNCTIONS

SPRAY WATER (OUTER) MASSAGE WATER (INNER)

COMBINATION WATER (OUTER + INNER)

IMPORTANT

Pressure & Temperature Requirements.

- Hot and cold water inlet pressures should be equal.
- Inlet pressure range: 150 -1000 kPa
 New Regulation: 500 kPa maximum operating pressure at any outlet within a building. (Ref. AS/NZS 3500.1-2003, Clause 3.3.4)
- Maximum hot water temperature : 80°C.



6

Distributed by: Caroma Industries Limited trading as Caroma Dorf ABN 35 000 189 499 Wall/tile face

13 mm