Caroma

Profile 4 Easy Height

Vitreous China 4.5/3 litre Dual Flush Connector Toilet Suite

CI/SfB |(74.1) | g3 | Date May 2015

Supersedes all previous issues

3.28.7





Caroma

Profile 4 Easy Height

Vitreous China 4.5/3 litre Dual Flush Cistern, Matched Pan, Plastic Seat and Connector Plate





The **Profile 4 Easy Height** connector suite is ideal for aged care applications where a raised seat height offers the advantage of easier use for persons with restricted movement. The **Profile 4 Easy Height** connector matched suite combines the Cosmo 4.5 litre pan and Profile cistern in an integrated system comprising of cistern with high performance outlet valve, seat and plastic connector plate, which conceals the flush pipe and water connection.

Pans: Cosmo 4.5 litre full flush washdown pan with open flushing rim.

Traps: S or P-trap unvented only.

Inlet: 50mm back inlet 40mm key seal is available if required.

Cisterns: Profile cistern (wall fixed version) – has a free fitting lid and is suitable for

domestic and light commercial applications.

Vandal Resistant Conversion Kit – A simple to install conversion is available for the standard mechanism to lock lid onto the cistern, recommended for use in

heavy use commercial areas. Code No.750109.

Inlet Valve Standard Bottom Inlet Cistern – available as right hand inlet which is Overflow: interchangeable and incorporates Apollo inlet valve. Internal overflow on

interchangeable and incorporates Apollo inlet valve. Internal overflow only.

Important: Working pressure minimum 30kPa to maximum 1000kPa flow

pressure. Rain water tank compliant.

Seat and Connector Plate: The $\pmb{\mathsf{Trident}}$ standard toilet seat or $\pmb{\mathsf{Profile}}$ soft close toilet seat and coupling kit

is supplied with the Profile 4 Easy Height connector suite.

Colours: White only.


Installation: The installation of the toilet suite shall be in accordance with the normal minimum

drainline grade requirements in AS/NZS 3500.2.

Dimensions: All dimensions are in millimetres and are subject to normal manufacturing

variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications

without notice.



270 Inlet

or overflow

approx

	
Inlet 55	400
	+
	185 470 Bottom inlet
165 Recommended (165 min - 265 max.)	- 1 1

Profile 4 Easy Height Connector Suites: Internal Overflow	Code No.
S trap with Trident Standard Seat	912443W
P trap with Trident Standard Seat	912453W
S trap with Profile Soft Close Seat	912443SC
P trap with Profile Soft Close Seat	912453SC

Note: All height dimensions to underside of pan, make allowance for bedding.

Bedding: The pan should be fixed to the floor with a sand cement mixture of 3:1 to a depth of 60mm. Do not use lime or fast drying cement in the bedding mixture. When bedded the back of the foot of the pan should be approximately 10mm above the finished floor.

Screw fixing: The pan should be bedded with an acetic cured silicone sealant and fixed with corrosion resistant screws and pan guard washers. Use Caroma screw fixing kit. Code No.601150.

445