caroma° cub∈³

Vitreous China Wall-Hung Box Rim Concealed Trap Pan

CI/SfB | (74.1) | g3 |
Date | July 2008

Supersedes all previous issues

4.04.1







Vitreous China Wall-Hung Box Rim Concealed Trap Pan





A minimalist styled box rim wall hung pan featuring smooth sculptured contours and advantages of unobstructed floor for easy cleaning. The pan features concealed shrouded trap and pan fixings providing optimum appearance to the wall and minimal projection from-the-wall dimension of 550mm. The **Cube** Pan has been developed to be installed directly to the wall using the Sanifix Bracketing System. The pan is suitable for domestic and commercial applications.

Pans: Cube 4.5 litre full flush, wall hung, wash down type with box rim.

Traps: P-trap only unvented – Code No.604300.

Inlet: 50mm back inlet for concealed cistern and flushvalve installation.

Cisterns and Caroma Concealed Cistern options available – Invisi II Under Counter/Inwall/ Induct/Inceiling Cisterns see Section 6 (available November 2008).

Invisi Inwall/Induct/Inceiling Cisterns, Compact Under Counter Dual

Flush Cistern, Slimline Induct Cisterns, Schell WC Flushvalve Inwall/

Induct see Section 6.

Fixing: Invisi II Wall Hung Pan Bracket options — D.403 Standard Code No.237403,

D.402 Undercounter Code No.237402 (available November 2008).
 Sanifix Wall Hung Pan Bracket options — D.788 Bolt Through the Wall Bracket Code No.687788, D.760 Chair Bracket Code No.687760, fixing pack Code No.687812, D.715 Cistern Chair Bracket Code No.687715, fixing pack

Code No.687812, **D.713 Cistern Chair Bracket** Code No.687715, lixing pack Code No.687812, **D.841 Stud Bracket** Code No.687841 aluminium for timber. **Note:** The bracket systems are suitable for installation only where non

compressible wall materials are used.

Seats: The Caroma Cube Soft Close seat is recommended. See Sheet 5.01 SEATS for

further details.

Colours: White only.

Installation: The installation of the toilet suite shall be in accordance with the normal minimum

drainline grade requirements in AS/NZS 3500.2.

Dimensions: All dimensions are in millimetres and are subject to normal manufacturing

variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications

without notice.

