Caroma

Urbane Invisi II

4.5/3 litre Dual Flush Toilet Suite with Urbane Wall Faced Box Rim Vitreous China Pan and Invisi II Cistern for Inwall, Under Counter, Induct or Inceiling applications CI/SfB |(74.1) | g3 | Date January 2014

Supersedes all previous issues

3.83.1







Caroma Urbane Invisi II

4.5/3 litre Dual Flush Toilet Suite with **Urbane Smartflush Vitreous China** Wall Faced Box Rim Pan and Invisi II Smartflush Cistern for Inwall, Under Counter, Induct or Inceiling applications





Pictured with Caroma Arc Soft Close seat

A classic designed wall faced concealed toilet suite comprises the Urbane pan and trusted Caroma Invisi II cistern suitable for use in domestic and commercial projects. The pan connection system includes the patented Caroma Uni-Orbital® Connector extends to any position in a 50mm radius, unlike traditional connectors that only move backwards and forwards. The setout range is from 60mm - 120mm with a recommended setout of 90mm. The smooth sided pan matched with the concealed cistern offer a seamless finish to your bathroom. Choose from a variety of buttons from the Caroma range to complete your desired look.

Urbane wall faced back inlet 4.5 litre full flush box rim pan

Traps: P-trap only unvented.

Inlet: Fully glazed 50mm back inlet for concealed cistern and flushvalve installation. Cisterns and Invisi II Cistern - suitable for inwall, under counter, induct and inceiling applications. For push button and access plate (supplied separately) options see Flushvalves:

chapter 6.15.1 CISTERNS of the Caroma Technical Manual.

The pan can be fixed to the floor by either bedding into mortar or using the D82

Concealed Fixing Bracket.

The Arc Soft Close thermoset toilet seat is provided as standard with the Seats:

Urbane suite. See chapter 5.01 SEATS of the Caroma Technical Manual for

further details.

Colours: White only.

Fixing:

Installation: The installation of the toilet suite shall be in accordance with the normal minimum

drainline grade requirements in AS/NZS 3500.2.

Dimensions: All dimensions are in millimetres and are subject to normal manufacturing

variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications

without notice

