

Care 660 Cleanflush™ Easy Height

Sanitary Compartment - Ambulant Applications
4.5/3 litre Vitreous China Wall Faced Close Coupled Toilet Suite



The **Care 660 Cleanflush™ Easy Height** suite offers an elevated pan for easy access to the seat for those with limited mobility. The added hygiene of the Cleanflush™ rimless flushing system makes the range ideal for hospital, aged care and commercial applications where the absolute highest levels of hygiene and efficient cleaning are required. The versatility of the Care 660 Cleanflush™ toilet suite makes it ideal for use by people with ambulant disabilities or in aged care applications.

- Important:** Reference must be made to **AS 1428.1-2009 with current amendments to determine circulation space, grab rail and installation requirements. The dimensions in this sheet may change with amendments to the standard.**
- Pan:** **Care 660 Cleanflush™ Easy Height** 4.5 litre full flush washdown rimless pan with a fully glazed trap.
- Traps:** Universal trap for S or P-trap installations.
- Cisterns:** **Care 660 Cleanflush™** cistern – has a free fitting lid and is suitable for domestic and light commercial applications. Available as internal overflow. Available in either back entry or bottom inlet versions. Cistern inlet stop valve is concealed within the cistern and is included (back entry version only).
Vandal Resistant Conversion Kit – A simple to install conversion kit is available for the standard mechanism to lock the lid onto the cistern, recommended for use in heavy duty commercial areas. Code No.750109. **Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant. Accurate wall setout for B.S.P. 1/2" Nipple water inlet connection is essential.**
- Buttons:** Round Button - Chrome (supplied). Other button options sold separately. See section 4 - CARE BUTTONS for further details.
- Seats:** Includes **Caravelle Care** double flap or single flap seat in Caroma White (W), Sorrento Blue (SB) or Anthracite Grey (AG). Solid section compression moulded seat with solid stainless steel hinges plus rotatable buffers for extra stability during sideways transport. See Section 3 - SEATS for further details.
- Colour:** White only.
- Installation:** The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.
- Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.



Uni-Orbital® Connector
Setout Range 60mm to 200mm
(up to 50mm sideways adjustment)

Pan foot level

140 recommended (range 60 – 200mm with Uni-Orbital® connector supplied - up to 50mm sideways adjustment)

Care 660 Cleanflush™ Easy Height Wall Faced Close Coupled Toilet Suite with Caravelle Care Seat

	Code No.	Seat Colour:
4.5/3 litre Back Entry Internal Overflow with Double Flap Seat	846910	W, SB or AG
4.5/3 litre Back Entry Internal Overflow with Single Flap Seat	846911	W, SB or AG
4.5/3 litre Bottom Inlet Internal Overflow with Double Flap Seat	846912	W, SB or AG
4.5/3 litre Bottom Inlet Internal Overflow with Single Flap Seat	846913	W, SB or AG

Setout position for 1/2" B.S.P. Nipple

Centre water back inlet connection

22mm approx. projection from wall

1/2" B.S.P. Nipple

Finished wall

415

870 approx.

185

190

Waste outlet

Pan seal

Uni-Orbital® connector can be positioned anywhere in shaded area in a 50mm arc

D82 Concealed Fixing Bracket

Note: All height dimensions to underside of pan, make allowance for bedding.
Bedding: The pan should be fixed to the floor with a sand cement mixture of 3:1 to a depth of 60mm. Do not use lime or fast drying cement in the bedding mixture. When bedded the back of the foot of the pan should be approximately 10mm above the finished floor.
Bracket fixing: The pan should be bedded with an acetic cured silicone sealant and fixed with the D82 bracket supplied.