

Sediment Removal Water Filter Cartridge

Product Code: 010555



Sediment Removal Water Filter Cartridge

PRODUCT SPECIFICATION

Product code	010555
Micron rating	5 micron
Min/max temperature	0-60°C
Min/max pressure	100-900 kPa
Min/max flow	0-26 litres per minute
Size	10 inch
Related products	136567 - Filter Housing

PRODUCT FEATURES

This cartridge can be used with many liquids and is very effective for sediment, rust, sand, silt and algae removal. These cartridges do not impart taste, odour or colour to the liquid being filtered. The polypropylene construction provides superior chemical resistance and is not prone to bacterial attack.

It has graded density filter design, means that the filter gets more dense towards the center of the filter. This increased depth ensures extremely high sediment reduction efficiencies and longer cartridge life.

PRODUCT APPLICATION

Drinking water, beverage industry, mineral water bottling, laboratory use, food industry, pre-filtration ahead of sub-micron filters or Reverse Osmosis and other industrial applications where low contamination levels are needed eg. plating solutions, oil, hydraulic fluid.

DIRECTIONS

Flush after installation for 5 minutes. For best results change cartridge every 6 months or when taste returns. Maximum life is 12 months.

Caution: Do not use with microbiologically unsafe water without adequate disinfection. Warning: For operation please observe manufacturer's instructions.



