



Jeda

4.5/3 litre Reduced Dual Flush Toilet Suite with Seat and Connector Plate



The **Jeda** connector toilet suite with its mid sized cistern is designed for retrofit installations and delivers a 4.5/3 litre dual flush system. Combined with the Stylus Concealed Connector 4.5 litre pan, the Jeda cistern is an integrated system comprising of cistern with high performance outlet valve, Beta seat and flush fitting connection plate, which conceals the flush pipe and water connection.

- Pan:** **Stylus Concealed Connector** 4.5 litre full flush washdown pan with open flushing rim.
- Traps:** S or P-trap unvented only.
- Inlet:** 50mm back inlet 40mm key seal is available if required.
- Cistern:** **Jeda** cistern – A one piece injection moulded tank with a well fitting removable lid housing and centrally positioned push buttons.
- Inlet Valve** **Standard Bottom Inlet Cistern** – available as right hand inlet which is interchangeable and incorporates Apollo inlet valve. Overflow is internal as standard, external overflow kit available. **Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant.**
- Overflow:**
- Seats:** The **Tasman II** toilet seat and connector plate is supplied with the **Jeda** suite.
- Colour:** White only.
- Installation:** The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.
- Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

Top view dimensions: 395 (width), 152 (seat width), 650 - 740 max. (height), 355 (base width).

Front view dimensions: 284 (fixing holes), 225 (inlet or overflow), 755 approx. (total height), 830 approx. (cistern height), 395 (base height).

Side view dimensions: 185 (cistern depth), 160 recommended (range 160mm - 250mm max.) (floor to pan).

Jeda Connector Toilet Suite with Seat:	Code No.
4,5/3 litre Bottom Inlet- Internal overflow with Tasman II seat	
S-trap with Tasman II seat	JD0110
P-trap with Tasman II seat	JD0120

Note: All height dimensions to underside of pan, make allowance for bedding.

Bedding: The pan should be fixed to the floor with a sand cement mixture of 3:1 to a depth of 60mm. Do not use lime or fast drying cement in the bedding mixture. When bedded the back of the foot of the pan should be approximately 10mm above the finished floor.

Bracket fixing: The pan should be bedded with an acetic cured silicone sealant and fixed with the bracket supplied.

Issue No. 1
Date of issue: 24.02.14